IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re the Patent of:)
HAMPDEN-SMITH et al.) REQUEST FOR CERTIFICATE OF) CORRECTION OF PATENT FOR PTO MISTAKE
Patent No.: 7,476,411 B1) (37 C.F.R. 1.322(a))
Issued: January 13, 2009)
Confirmation No.: 4450)
Atty. File No.: 41890-00790))·
For: "DIRECT-WRITE DEPOSITION OF PHOSPHOR POWDERS"	,
Commissioner for Patents	
P.O. Box 1450	
Alexandria, VA 22313-1450	

Dear Sir:

This is a request for a Certificate of Correction for PTO mistake under 37 C.F.R. 1.322(a). The errors in the patent are obvious typographical errors or omissions and the correct wording can be found in the original specification at Page 3, line 30, Page 14, line 19, and Page 51, line 29, or the Office Action dated August 12, 2002. Attached is form PTO 1050 in duplicate along with copies of documentation that unequivocally supports patentee's assertion(s).

Respectfully submitted,

MARSH FISCHMANN & BREYFOGLE LLP

By: /David F Dockery Reg No 34323/ David F. Dockery Registration No. 34,323 8055 East Tufts Avenue, Suite 450 Denver, Colorado 80237 Telephone: 303-770-0051 Facsimile: 303-770-0152

Date: January 29, 2009

Notice of References Cited				Reexamina		eyPatent Under ation I-SMITH ET AL.	
			Exami	ner	Art Unit	Page 1 of 1	
				K Talbot	1762		
_				U.S. PATENT D	OCUMENTS		
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY		Name		Classification
7	A	US-5,644,193 A	07-1997	Matsuda et al.			313/486
7	В	US-6,197,218.B1	03-2001	Hampden-Smit	hetal.		252/301.36
1	c	US-6,193,908 B1	02-2001	Hampden-Smit	thetal.		252/301.35
7	D	US- 5,932,139	08-1999	OShina	eTal		252/301.16
7	E	US-					
\neg	F	US-					
	G	US-					
	н	US-					
	1	US-					
	J	US-					
	к	US-					
_	L	US-					<u> </u>
_	М	US-					
_			Date	FOREIGN PATE			Classification
*		Document Number Country Code-Number-Kind Code	MM-YYYY	Country		Name	Classification
Г	N	11-46019	02-1999	Japan			
	0						
Г	Р						
	Q						
Г	R						
	s						+
	Т						<u> </u>
_					DOCUMENTS	or Volume Partinent Part	es)
*	+	Include as applicable: Author, Title Date, Publisher, Edition or Volume, Perthent Pages)					
1	U						
-	V						
-	V						

"A copy of this reference is not being furnished with this Office action, (See MPEP § 707.05(a).) Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

that secured articles can be easily produced using luminescent compositions that are not normally visible but are detectable using ultraviolet light or other means.

BRIEF DESCRIPTION OF THE DRAWINGS

- 5 Fig. 1 is a process block diagram showing one embodiment of the process of the present invention.
 - Fig. 2 is a side view in cross section of one embodiment of aerosol generator of the present invention.
- . Fig. 3 is a top view of a transducer mounting plate showing a 49 transducer array 10 for use in an aerosol generator of the present invention.
 - Fig. 4 is a top view of a transducer mounting plate for a 400 transducer array for use in an ultrasonic generator of the present invention.
 - Fig. 5 is a side view of the transducer mounting plate shown in Fig. 4.
- Fig. 6 is a partial side view showing the profile of a single transducer mounting 15 receptacle of the transducer mounting plate shown in Fig. 4.
 - Fig. 7 is a partial side view in cross-section showing an alternative embodiment for mounting an ultrasonic transducer.
 - Fig. 8 is a top view of a bottom retaining plate for retaining a separator for use in an aerosol generator of the present invention.
- 20 Fig. 9 is a top view of a liquid feed box having a bottom retaining plate to assist in retaining a separator for use in an aerosol generator of the present invention.
 - Fig. 10 is a side view of the liquid feed box shown in Fig. 9.
 - Fig. 11 is a side view of a gas tube for delivering gas within an aerosol generator of the present invention.
- 25 Fig. 12 shows a partial top view of gas tubes positioned in a liquid feed box for distributing gas relative to ultrasonic transducer positions for use in an aerosol generator of the present invention.
 - Fig. 13 shows one embodiment for a gas distribution configuration for the aerosol generator of the present invention.
- Fig. 14 shows another embodiment for a gas distribution configuration for the aerosol generator of the present invention.
 - Fig. 15 is a top view of one embodiment of a gas distribution plate/gas tube assembly of the aerosol generator of the present invention.

to disperse more readily in a liquid suspension and impart advantageous flow characteristics to the suspension, particularly for deposition using a direct-write tool. For a given level of solids-loading, a liquid suspension of spherical particles will have a lower viscosity than a printing composition having non-spherical particles. Spherical particles are 3 also less abrasive than jagged particles, reducing the amount of abrasion and wear on the direct-write tool.

In addition, the phosphor particles according to the present invention are substantially unagglomerated, that is, they include substantially no hard agglomerates of particles. Hard agglomerates are physically coalesced lumps of two or more particles that 10 behave as one large particle. Agglomerates are disadvantageous for direct-write applications since large agglomerates can clog the orifice of the tool and can affect the minimum average line width that can be deposited with the tool. It is preferred that no more than about 1.0 weight percent of the phosphor particles of the present invention are in the form of hard agglomerates. More preferably, no more than about 0.5 weight percent 15 of the phosphor particles are in the form of hard agglomerates.

A preferred method for forming the phosphor particles according to the present invention is to utilize a spray pyrolysis technique. A preferred spray pyrolysis technique is described in detail in U.S. Patent Application Serial No. 09/030,057, which is commonly owned with the present application and which is incorporated herein by reference in its 20 entirety.

Generally, spray pyrolysis involves the generation of an aerosol of liquid precursors to the phosphor compound. Phosphor powders can be produced by spray pyrolysis that have high purity and a homogenous chemical composition. Preferably, the powders are produced in a substantially unagglomerated state without the necessity of a milling step to reduce primary particle size or agglomeration. Advantageously, the morphology of the particles can be controlled such that hollow and or porous particles can be produced as well as substantially dense particles.

Spray pyrolysis includes atomizing the precursor solution to form droplets, preferably with an ultrasonic atomizer. The droplets are then passed through a hot-wall reactor, such as a tubular furnace, in which the solvent evaporates and the precursors react to form the desired phosphor compound. The particles are then collected, for example in a heated filter. The average particle size can be tightly controlled by adjusting process parameters such as the concentration of precursor in solution and the frequency of the ultrasonic

deposition technique. However, the method of the present invention wherein fine phosphor particles are deposited using a direct-write tool, can be used to form the layer at a reduced cost. It is particularly advantageous to form a TFEL device by incorporating soluble molecular precursors into the liquid vehicle, as is discussed above. Thus, a phosphor 5 compound particle in a liquid vehicle including precursors to the phosphor compound can be deposited using a direct-write tool. Freferred phosphor compounds for TFEL applications include ZnS:Cu, SrGa, S.:Ce or Eu and SrS:Cu.

The method of the present invention is also applicable to electroluminescent lamps. Electroluminescent lamps are formed on a rigid or flexible substrate, such as a polymer 10 substrate, and are commonly used as back lights for membrane switches, cellular phones, watches, personal digital assistance and the like. A simple electroluminescent lamp is schematically illustrated in Fig. 39. The device 1140 includes a phosphor powder/polymer composite 1142 sandwiched between two electrodes 1144 and 1146, the front electrode 1144 being transparent. The composite layer 1142 includes phosphor particles 1148 15 dispersed in a polymer matrix 1150. Electroluminescent lamps can also be formed on rigid substrates, such as stainless steel, for use is highway signage and similar devices. The methodology according to the present invention can be used to form discrete patterns of such phosphor powders in electroluminescent lamps, such as for text or aesthetic purposes.

20

The present invention is also applicable to flat panel displays. Flat panel displays offer many advantages over CRTs including lighter weight, portability and decreased power requirements. One type of flat banel display is a field emission display (FED). These devices advantageously eliminate the size, weight end power consumption problems of CRT's while maintaining comparable image quality, and therefore are particularly useful 25 for portable electronics, such as for laptop computers. FED's generate electrons from millions of cold microtip emitters with low power emission that are arranged in a matrix addressed array with several thousand tip emitters allocated to each pixel in the display. The microtip emitters are typically located approximately 0.2 millimeter from a cathodoluminescent prosphor screen, which generates the display image. This allows for 30 a thin, light-weight display.

Fig. 40 illustrates a high-magnification, schematic cross-section of an FED device according to an embodiment of the present invention. The FED device 1080 includes a plurality of microtip emitters 1082 mounted on a cathode 1084 which is attached to a

D---

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.
(Also Form PTO-1080)

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : 7,476,411 B1	1 age 01
APPLICATION NO.: 09/495,141	
ISSUE DATE : January 13, 2009	
INVENTOR(S) : HAMPDEN-SMITH et al.	
It is certified that an error appears or errors appear in the above-identified patent and t is hereby corrected as shown below:	hat said Letters Patent
Title Page, (56) References Cited, insert:5,644,193 A 7/1997 Matsuda et al	
Column 3, line 17, delete "an other" and insert thereforanother Column 10, line 26, delete "tis" and insert thereforits Column 36, line 54, delete "cathoduluminescent" and insert thereforcathodoluminescent	

MAILING ADDRESS OF SENDER (Please do not use customer number below):

David F. Dockery, Esq. Marsh Fischmann & Breyfogle LLP

8055 East Tufts Avenue, Suite 450

This collection of information is required by 37 CFR 1.322, 1.323, and 1.324. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application, Confidentially is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is either to late 1.0 hour to complete, including gathering, preparing, and submitting the completed application from to the USPTO. Time will vary depending upon the individual case. Any comments on the arount of time yet require to complete in formation of the require to complete in formation of the complete in the submitted of the complete in the submitted in the submitted of the complete in the submitted in the submitted of the complete in the submitted in the submitted of the complete in the submitted in the submitted of the submitted in the submitted in the submitted of the submitted in t

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

- The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
- A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
- A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the
- A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
- A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
- A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
- 7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
- 8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S. C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
- A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.